

DATE : 24 JUL 07  
DESIGNED: RJH  
DRAWN : MSM  
CHECKED : TMK  
QA / QC : MTC


[illegible]DATE \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**FIRST & MAIN**  
PHASE 1  
BLACKSBURG, VIRGINIA


## SITE DETAILS 1

DOCUMENT NO.  
**22559 – 210**

SHEET  
**C1.18**



**PARKING BLOCK**  
NOT TO SCALE



FOR ALL SPACES TO BE DESIGNATED AS ACCESSIBLE, THE VIRGINIA STANDARD "RESERVED PARKING" SIGN SHALL BE INSTALLED, AS WELL AS THE STANDARD "PENALTY, TOW-AWAY ZONE" SIGN.

FOR SPACES DESIGNATED ON  
PLAN AS VAN ACCESSIBLE,  
PROVIDE "VAN ACCESSIBLE"  
SIGN WITH MINIMUM 2" HIGH  
LETTERING MOUNTED  
UNDERNEATH RESERVED  
PARKING SIGN.


SIGN(S) SHALL BE MOUNTED TO 2" DIAM. FIELD PAINTED STEEL TUBE (UNLESS SPECIFIED TO BE WALL MOUNTED). SET PIPE IN 12" DIAMETER BY 18" DEEP A3 CONCRETE BASE, RECESSED 6" BELOW FINISHED GRADE. COLOR AND PAINT TO BE SELECTED BY OWNER OR ARCHITECT.

SIGN(S) SHALL BE MOUNTED WITH THE BOTTOM OF THE SIGN(S) NO LESS THAN 4' AND NO HIGHER THAN 7' ABOVE ABOVE THE FINISHED GRADE..

THE REQUIRED ITEMS MAY BE CONTAINED ON ONE OR MULTIPLE SIGNS. SUBMIT SHOP DRAWING(S) FOR SIGNS.

SIGN(S) SHALL COMPLY WITH THE LATEST EDITION OF UFAS (UNIFORM FEDERAL ACCESSIBILITY STANDARDS), VUSBC (VIRGINIA UNIFORM STATEWIDE BUILDING CODE), AND THE CODE OF VIRGINIA SECTION 36-99.11.



## HANDICAP PARKING SIGN



## STANDARD CURB & GUTTER

NOT TO SCALE

**REVERSE PITCH**  
**CURB & GUTTER**  
NOT TO SCALE



NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWINGS.
3. DIMENSIONS APPLY FOR ALL BASIS. OPTIMAL HEIGHT OF 27" (686MM) IS AVAILABLE.
4. THE MODEL NUMBERS INDICATE THE NUMBER OF BUSES EACH BLUE ROCK HOLDS.
5. CONTRACTORS NOTE: (FOR PRODUCT AND COMPANY INFORMATION VISIT [www.Cabletek.com/inf](http://www.Cabletek.com/inf))

REFERENCE NUMBER: 096-001C

BR SERIES BIKE RACKS

TOWN ENGINEER	DATE
TOWN PLANNER	DATE

